

## Architectural B LED TAPE LIGH

DATE:

PROJECT:

TYPE:



Architectural grade COB tape light designed for applications that require high output and seamless light.

## Features


- Lumens per foot: L0-210 / M0 -290 / H0 - 454 / VH0 - 550
- . Applications that need higher-intensity lighting
- Industry-leading 90 CRI
- . Higher efficiency rate (reduces 25% of heat)
- . High-uniformity, even at close working distances
- Superior thermal performance, increased lifetime, stability and reliability

## **Technical Information**

	L0-2.4W / M0-3W / H0-4.5W / VH0-5.8W		
Input Voltage	24V DC / 12V DC		
Tape Height	0.1 Inch		
Beam Angle	120'		
Field Cuttable	Every 1 Inches		
Max Run Length	50 FT (24V only)		
Diode Spacing	0.3 Inch		

Diode Type	2835 SMD	
Mounting	3M™ Self-Adhesive Tape	
Spool Lengths	16.4 FT - Custom	
Location	Indoor AND Outdoor options	
Certifications	UL Listed, CE, RoHS	
Warranty	2 Year Limited	

## **Ordering Code**



MODEL	VOLTAGE	ССТ	LENGTH	RATING
SL-COB-LED-LO	12V ● 12V DC	<b>27κ ●</b> 2700K	Blank (16.4 FT)	IP20 (Indoor)
SL-COB-LED-MO	<b>24</b> V ● 24∨ DC	<b>зок ●</b> 3000К	Custom	IP65 (Outdoor)
SL-COB-LED-HO		<b>35κ ●</b> 3500K	(Consult factory)	
SL-COB-LED-VHO		<b>40</b> κ ● 4000K		
		<b>50κ ●</b> 5000K		
		<b>ртw ●</b> Dim-to-Warm		

SPECIFICATIONS SUBJECT TO CHANGE, CONSULT FACTORY WHEN CRITICAL.

spec-lighting.com

244 Fifth Ave, Suite L277 New York, NY 10001

പ്

sales@spec-lighting.com  $(\boxtimes)$