

# FAL

<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>

## STANDARD SPECIFICATIONS

### DIFFUSER

Glass diffuser. Can be mounted on ceiling or wall in all orientations

### LED PERFORMANCE-3000K STANDARD

120-277V-3000K, 82CRI- L80 rating -60,000hrs-L70 rating (projected) - 100,000 hrs Operating ambient temperature:-20°C/-4°F-40°C/104°F


Delivered 3000K lumens noted. Consult factory for performance of all CCTs.

48"-2100 Lumens Dimmable (ELV).

For damp locations.

### MOUNTING

Supplied with a canopy cover plate in case of junction box mounting



## ORDERING INFORMATION

**FAL-** \_\_\_\_\_  
 Model                    2.                    3.                    4.                    5.

### 2. FINISH

#### STANDARD

- BN** Brushed Nickel
- CH** Chrome
- BK** Black
- WH** White

#### CUSTOM

Consult factory for custom finishes.

### 3. WATTAGE

- 48"** 20 W LED
- XX** Custom Size

### 4. COLOR TEMPERATURE

- 27K** 2700K
- 30K** 3000K
- 35K** 3500K
- 40K** 4000K

### 5. Driver Option

- ELV** ELV Dimming
- ND** Non Dimming