

MUR

| |
|---------------|
| PROJECT: |
| MODEL #: |
| FIXTURE TYPE: |

STANDARD SPECIFICATIONS

CONSTRUCTION

Aluminum hardware with glass diffuser.

DIFUSSER

Milk glass diffuser. Can be mounted on ceiling or wall in all orientations.

LED PERFORMANCE – 3000K STANDARD

- 120-277V-3000K, 82CRI- L80 rating - 60,000hrs - L70 rating (projected) - 100,000 hrs.
- Operating ambient temperature:-20° C / -4° F- 40° C / 104° F.
- 1950 lumens at 14W, 2950 lumens at 20W, 3950 lumens at 25W.

UL Listed for dry and damp locations.



MOUNTING

Directly to j-box (by others). Mounting hardware included.

USE

Healthcare, Education, Multi-Family Residential
Condominiums, Retail, Corporate, Hospitality



ORDERING INFORMATION

| MUR | | | | | |
|--|---|------------------------------|--------------------|-----------------------|------------------------------|
| 1 | 2 | 3 | 4 | 5 | 6 |
| 2. FINISH | | 3. SIZE | 4. WATTAGE | 5. COLOR TEMP. | 6. DRIVER OPTION |
| BN Brushed Nickel | | 24" 24" (1950 Lumens) | 14 14W LED | 27K 27000K | ND Non Dimming |
| CH Chrome | | 40" 40" (2950 Lumens) | 20 20 W LED | 30K 30000K | D-1% 0 – 10 V Dimming |
| BLK Black | | 50" 50" (3950 Lumens) | 25 25 W LED | 35K 35000K | ELV ELV Dimming |
| WH White | | | | 40K 40000K | |
| AL Aluminium | | | | | |
| CUSTOM | | | | | |
| Consult Factory for custom finishes and sizes. | | | | | |