

PARETE

PROJECT:

MODEL #:

FIXTURE TYPE:

STANDARD SPECIFICATIONS

FRAME

Die-formed steel with reflective white polyester powder finish and silicone gasket.

DIFFUSER

Translucent white or grey acrylic diffuser. Beautiful yet extremely tough and attractive.

LED PERFORMANCE - 3000K STANDARD

120-277V - 3000K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs

Amperage rated @110Vinput

Operating ambient temperature: -20°C / -4°F - 40°C/104°F

Delivered 3000K lumens noted. Consult Spec Lighting for performance of all CCTs.


9W - 9W nominal, .10 A input - 797 lm. Dimmable (0-10V, ELV).

16W - 16W nominal, .15 A input - 1633 lm. Dimmable (0-10V, ELV).

24W - 23W nominal, .20 A input - 2240 lm. Dimmable (0-10V, ELV).

MOUNTING

Directly to j-box (by others). Mounting hardware included.



ORDERING INFORMATION

PARE-

Model 2. 3. 4. 5.

2. FINISH

STANDARD

GR Grey
WH White

CUSTOM

Consult factory for custom finishes

3. WATTAGE

9 9W LED
16 16W LED
24 23W LED

4. COLOR TEMPERATURE

27K 2700K
30K 3000K
35K 3500K
40K 4000K

5. Driver Option

ND Non Dimming
D-1% 0-10V Dimming
ELV ELV Dimming